



## 2785Z1

### Headlamp

Peli 2785Z1 is certified by ATEX Zone 1 (Cat. 2) therefore can be used in potentially hazardous areas often found in the Fire & Safety, Oil & Gas, Petrochemical, Pharmaceuticals and other hazmat industries. This new safe headlamp brings a high performance of 215 lumens and 100 hours of burn time. This is the perfect combination of Safety, Power and Long burn time which will support all professionals' needs for hands free lighting. This headlamp provides four modes of illumination: Main, Downcast, Flashing, and the combination of Main/Downcast LED modes. The focused Main LED illuminates everything in front providing a great distance beam of 108 meters, while the Downcast LED projects a dispersed beam set at a 45° downward angle. This Downcast beam facilitates safer illuminated pathways, reading capability and convenient face to face applications. Options are plentiful as each mode is provided in an easy to select high, medium or low setting. It offers a pivoting 60° head to direct the light where needed.

- 4 AA Batteries Included
- Pivoting Head For Directional Beam (60°)
- Rear Mounted Red LED
- Dual Beams including Downcast LED Technology
- 3 Light Levels
- Full Time Battery Level Indication
- Cloth and Rubber Straps Included



### DIMENSIONS

<b>Length</b>	3.00" (7.6 cm)
---------------	----------------

### MATERIALS

<b>Body</b>	Anti-static Impact Modified PC/PBT
<b>O-Ring</b>	Gasket
<b>Lens</b>	Polycarbonate (PC)
<b>Shroud</b>	Anti-static Impact Modified PC/PBT

### COLOURS

 Black	 High Visibility Yellow
---	--

### LIGHT SPECS

<b>Lamp Type</b>	LED
<b>Lamp Secondary Type</b>	LED

### POWER

<b>Battery Size</b>	AA
<b>Battery Type</b>	Alkaline
<b>Battery Quantity</b>	4
<b>Batteries Included</b>	yes
<b>Battery Level Indicator</b>	3 Blue LEDs
<b>Volts</b>	6.0v

WEIGHT






Weight With Batteries	8.8 oz (249 gr)
Weight Without Batteries	6.6 oz (187 gr)

SWITCH

Switch Type	Rotary / Push Button
Light Modes	High / Medium / Low / Downcast / Spot / Flashing

CERTIFICATIONS

ATEX Zone 1

FL1 STANDARD	MAIN HIGH	MAIN MED	MAIN LOW
	215 LUMENS	106 LUMENS	22 LUMENS
	5h 0mins	13h 0mins	98h 0mins
	108m	76m	34m
	2911cd	1445cd	290cd
	IP54		

ACCESSORIES



**0783**  
Head Strap Retainers

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 03-28-24*