



3410M

Right Angle Light

The most versatile pro-grade flashlight in the world, with magnet clip.

The 3410M (magnet version) is the ultimate compact work light. Molded from "glow in the dark" photoluminescent material, this light is easy to find even when it's off. The 3410M is equipped with both a spot and flood LED for close-up as well as distance, so you can have wide area light in the immediate work area and still penetrate darkness hundreds of yards away. It can be activated to run one or both LEDs with 3 levels of brightness. The articulating head and built-in clip allows the light to be directed wherever it is needed, while a heavy duty magnet allows the light to be snapped to steel surfaces. The Peli 3410M- a professional grade multi-task lighting tool that will help you get the job done- under any circumstances.

- Articulating Light Head
- "Glow in the Dark" Body
- Attached clip with integrated magnet
- Security Lanyard
- 3 Modes: High / Medium / Low
- 4 modes: spot/flood, spot, flood, flashing
- Split ring installed



DIMENSIONS

Length	7.44" (18.9 cm)
--------	-----------------

MATERIALS

Body	Photo luminescent Polycarbonate (PC)
O-Ring	NBR
Lens	Clear Polycarbonate (PC)
Shroud	Photo luminescent Polycarbonate (PC)
Clip	Photo luminescent Polycarbonate (PC)
Contact Spring Retainer	Stainless Steel / Phosphore Bronze / Brass Nickel Plate

COLOURS

	Photoluminescent
---	------------------

LIGHT SPECS

Lamp Type	LED
Lamp Secondary Type	LED

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	3
Volts	4.5v

WEIGHT

Weight With Batteries	9.9 oz (281 gr)
-----------------------	-----------------

**Weight Without
Batteries**

7.4 oz (210 gr)

SWITCH

Switch Type

Push Button

Light Modes

High / Medium / Low / Flashing

FL1 STANDARD	MAIN HIGH	MAIN MED	MAIN LOW
	653 LUMENS	97 LUMENS	25 LUMENS
	5h 0mins	19h 0mins	61h 0mins
	184m	67m	34m
	8504cd	1129cd	292cd
	IPX8 (1m)		

ACCESSORIES



2469P

Replacement Battery

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

