



## iM2500

### Storm

Carry-On Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

The Peli™ iM2500 Storm Case is designed to meet the maximum airline carry-on size, allowing you to keep your sensitive gear securely by your side while traveling. Be sure to verify the specific size requirements with your airline, as they may vary.

- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin
- Check the size allowance of your airline




## CONFIGURATIONS



**iM2500**  
Standard



**iM2500-X0000**  
No Foam



**iM2500-X0002**  
With Padded Dividers



**iM2500-X0006**  
With TrekPak Divider System



**iM2500-X0001**  
With Foam

## DIMENSIONS

<b>Interior (L×W×D)</b>	20.50 x 11.50" x 7.20 (52.1 x 29.2 x 18.3 cm)
<b>Exterior (L×W×D)</b>	21.70 x 14.10" x 8.90 (55.1 x 35.8 x 22.6 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	5.20" (13.2 cm)
<b>Total Depth</b>	7.2" (18.3 cm)
<b>Int Volume</b>	0.98 ft <sup>3</sup> (0.028 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.28" (0.7 cm)

## MATERIALS

<b>Body</b>	Injection Molded HPX™ high performance resin
<b>Latch</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Latch (Alt)</b>	Xenoy - Polyester/Polycarbonate blend
<b>O-Ring</b>	EPDM
<b>Pins</b>	Stainless Steel
<b>Pins (Alt)</b>	Aluminum
<b>Foam</b>	1.3/1.35 polyester
<b>Purge Body</b>	Valox - Polybutylene Terephthalate (PBT)
<b>Purge Body (Alt)</b>	Xenoy - Polyester/Polycarbonate blend

**Purge Vent**

Gortex membrane

COLOURS

■ Black

■ OD Green

■ Yellow

WEIGHT

<b>Weight With Foam</b>	13.70 lbs (6.21 kg)
<b>Weight Empty</b>	11.10 lbs (5.03 kg)
<b>Buoyancy</b>	62.56 lbs (28.38 kg)
<b>Master Pack Weight</b>	42.10 lbs (19.1 kg)

TEMPERATURE

<b>Minimum Temperature</b>	-20°F (-28.9 °C)
<b>Maximum Temperature</b>	140°F (60 °C)

CERTIFICATIONS

**IP67**

OTHER

<b>Extendable Handle</b>	yes
<b>Master Pack</b>	3
<b>Military</b>	yes

ACCESSORIES



**iM2500-UTILITYORG**  
Utility Organizer



**iM2500-FOAM**  
5 pc. Replacement Foam Set




**iM2500-DIV**  
Padded Divider Set



**iM-STRAP-S-VER2**  
Padded Shoulder Strap




**iM-LIDSTAY**  
Lid Stay



**iM2500-M4-BEZEL-L**  
Lid Bezel Kit (Metric)



**iM2500-MBEZ-B**  
Base Bezel Kit (Metric)



**iM2500-TREK**  
TrekPak Case Divider Kit



**1555TPDIV**  
Extra TrekPak Dividers



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**IM2720TPDIV**  
Extra TrekPak Dividers

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 04-26-26*