



iM2435

Storm

Top Loader Case

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**
- Retractable extension trolley handle
- Two Press & Pull Latches
- In-line Wheels
- O-ring seal
- Lightweight Strong HPX® Resin
- Two stainless steel padlock protectors



CONFIGURATIONS



iM2435
Standard



iM2435-X0000
No Foam



iM2435-X0002
With Padded Dividers & Lid Organizer



iM2435-X0001
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 17.50 x 6.50" x 15.50 (44.5 x 16.5 x 39.4 cm) |
| Exterior (L×W×D) | 18.63 x 9.25" x 16.50 (47.3 x 23.5 x 41.9 cm) |
| Lid Depth | 2.00" (5.1 cm) |
| Bottom Depth | 13.50" (34.3 cm) |
| Total Depth | 15.5" (39.4 cm) |
| Int Volume | 1.02 ft ³ (0.029 m ³) |
| Padlock Hole Diameter | 0.37" (0.9 cm) |

MATERIALS

| | |
|-------------------------|--|
| Body | Injection Molded HPX™ high performance resin |
| Latch | Valox - Polybutylene Terephthalate (PBT) |
| Latch (Alt) | Xenoy - Polyester/Polycarbonate blend |
| O-Ring | EPDM |
| Pins | Stainless Steel |
| Pins (Alt) | Aluminum |
| Foam | 1.3/1.35 polyester |
| Purge Body | Valox - Polybutylene Terephthalate (PBT) |
| Purge Body (Alt) | Xenoy - Polyester/Polycarbonate blend |
| Purge Vent | Gortex membrane |

COLOURS

■ Black

WEIGHT

Weight With Foam 11.15 lbs (5.06 kg)
Weight Empty 10.00 lbs (4.54 kg)
Buoyancy 56.70 lbs (25.72 kg)

TEMPERATURE

Minimum Temperature -20°F (-28.9 °C)
Maximum Temperature 140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Extendable Handle yes
Master Pack 1
Military yes

ACCESSORIES



iM2435-FOAM
8 pc. Replacement Foam Set



iM2435-DIV-LIDORG
Divider Set & Lid Organizer



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 06-17-26