# CLASSIC-V-SERIES-9U

## Classic V

9U



- Engineered to provide secure transport for rack mountable electronics
- Available in 3U, 4U, 5U, 7U, and 9U
- Equipment payload weight ranges for 3U – 5U = 80-100 lbs. (36-45 kg) per case
- Equipment payload weight ranges for 7U – 9U = 100-170 lbs. (45-77 kg) per case
- Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware
- Black stainless steel handles, and 1 comfort grip plastic handle on the 2" lid for rolling the case
- Molded stacking ribs and coupling catches to secure cases when stacked
- Lid hangers for lid storage while in use
- 19" (48 cm) wide, 33" (83 cm) deep fixed square hole frame for universal equipment fit
- Choice of SAE 10-32 or Metric M6 clip nuts
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- 2 edge casters on 5" lid
- RoHs compliant

## DIMENSIONS

| | |
|---|---|
| **Exterior (L×W×D)** | 45.80 x 27.00" x 24.30 (116.3 x 68.6 x 61.7 cm) |
| **Rack Height** | 15.75" (40 cm) |
| **Rack Depth** | 33.00" (83.8 cm) |
| **Interior Lid Depth** | 2.50" (6.4 cm) |
| **Interior Back Lid Depth** | 5.25" (13.3 cm) |

## MATERIALS

| | |
|---|---|
| **Body** | RotoMolded Polyethylene |
| **O-Ring** | Silicone Sponge |
| **Purge Body** | Aluminum |
| **Hardware** | Stainless Steel (Black Oxide) / RoHs Nickel Black |
| **Frame** | Steel (Clear Coated) |

## COLOURS

Black

## WEIGHT

| | |
|---|---|
| **Weight** | 72.00 lbs (32.66 kg) |

**Peli**
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

*Document created on 10-30-26*