



## 1650EU Protector

The Peli 1650 is a large sized protector case that comes with three comfortable, fold down, rubber over-moulded carrying handles as well as a retractable handle and 4 strong polyurethane wheels with stainless steel bearings. Like all other Peli Protector cases, this rugged case is also designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid and stainless steel hardware. Rugged, uncompromising and trusted, Peli cases protect what matters to you, from the everyday to the extraordinary. Peli Protector Cases are made with copolymer polypropylene and cutting edge technology, which makes them virtually indestructible and resistant to the most extreme conditions. Proven for over 45 years in the most demanding environments. Engineered and manufactured in the U.S and in Germany. Guaranteed for Life and sustainable due to its long life.

- **4 strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Made in Germany



### CONFIGURATIONS



**1650EU**  
Standard



**1654**  
With Padded Dividers



**1650NF**  
No Foam



**1650WF**  
With Foam

### DIMENSIONS

|                              |  |
|------------------------------|--|
| <b>Interior (L×W×D)</b>      | 28.41 x 17.40" x 10.64 (72.2 x 44.2 x 27 cm)   |
| <b>Exterior (L×W×D)</b>      | 31.55 x 20.51" x 12.47 (80.1 x 52.1 x 31.7 cm) |
| <b>Lid Depth</b>             | 1.81" (4.6 cm)                                 |
| <b>Bottom Depth</b>          | 8.84" (22.5 cm)                                |
| <b>Total Depth</b>           | 10.65" (27.1 cm)                               |
| <b>Int Volume</b>            | 3.04 ft <sup>3</sup> (0.086 m <sup>3</sup> )   |
| <b>Padlock Hole Diameter</b> | 5/16" (12.7 cm)                                |

### MATERIALS

|              |               |
|--------------|---------------|
| <b>Body</b>  | Polypropylene |
| <b>Latch</b> | ABS           |

|                   |                                |
|-------------------|--------------------------------|
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLOURS

|   |  |  |
|---|--|--|
|  Black |  Desert Tan |  OD Green |
|---|--|--|

## WEIGHT

|                         |                      |
|-------------------------|----------------------|
| <b>Weight With Foam</b> | 28.06 lbs (12.73 kg) |
| <b>Weight Empty</b>     | 24.03 lbs (10.9 kg)  |
| <b>Buoyancy</b>         | 181.00 lbs (82.1 kg) |

## TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 190°F (87.8 °C) |

## CERTIFICATIONS

**IP67**  
**MIL C-4150J**  
**Def Stan 81-41**  
**ATA 300**

## OTHER

|                          |     |
|--------------------------|-----|
| <b>Wheels</b>            | 4   |
| <b>Extendable Handle</b> | yes |
| <b>Master Pack</b>       | 1   |
| <b>Nameplate</b>         | yes |
| <b>Reduced Area</b>      | yes |
| <b>Military</b>          | yes |

## ACCESSORIES



**1651**  
4 pc. Replacement Foam Set



**1653**  
Replacement O-ring



**1655**  
Padded Divider Set



**1659**  
Photo/Lid Organizer




**1650EUTP**  
TrekPak Case Divider Kit



**1507QM**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 06-10-26*