



## 1460 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available with EMS Organizer and Dividers
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### CONFIGURATIONS



**1460**  
Standard



**1460AALG**  
With Custom Foam for 9430 / 9435



**1460NF**  
No Foam



**1460WF**  
With Foam

### DIMENSIONS

|                              |                                               |
|------------------------------|-----------------------------------------------|
| <b>Interior (LxWxD)</b>      | 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) |
| <b>Exterior (LxWxD)</b>      | 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)  |
| <b>Lid Depth</b>             | 4.91" (12.5 cm)                               |
| <b>Bottom Depth</b>          | 6.01" (15.3 cm)                               |
| <b>Total Depth</b>           | 10.92" (27.7 cm)                              |
| <b>Int Volume</b>            | 1.16 ft³ (0.033 m³)                           |
| <b>Padlock Hole Diameter</b> | 0.31" (0.8 cm)                                |

### MATERIALS

|               |                 |
|---------------|-----------------|
| <b>Body</b>   | Polypropylene   |
| <b>Latch</b>  | EXL             |
| <b>O-Ring</b> | Polymer         |
| <b>Pins</b>   | Stainless Steel |

|                   |                                |
|-------------------|--------------------------------|
| <b>Foam</b>       | Polyurethane                   |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLOURS

■ Black

## WEIGHT

|                         |                     |
|-------------------------|---------------------|
| <b>Weight With Foam</b> | 12.48 lbs (5.7 kg)  |
| <b>Weight Empty</b>     | 8.75 lbs (4 kg)     |
| <b>Buoyancy</b>         | 82.00 lbs (37.2 kg) |

## TEMPERATURE

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 210°F (98.9 °C) |

## CERTIFICATIONS

**IP67**

## OTHER

|                 |     |
|-----------------|-----|
| <b>Military</b> | yes |
|-----------------|-----|

## ACCESSORIES



**1461**  
6 pc. Replacement Foam Set



**1463**  
Replacement O-ring



**1507**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 05-20-24*