



2315Z0

The hazard horizon is bright. With ATEX Zone 0 (Category 1) Safety Certification , 115 lumens, 75 meters of spot beam distance and an IPX8 Waterproof rating, the Peli™ 2315Z0 flashlight stretches light across dark, hazardous environments without being a source of ignition.

Engineered with an aluminum core and ABS overmoulded plastic, this flashlight is built for rough handling and can survive hard drops. Plus, the sturdy clip attaches to a work vest for fast access and the tail switch activates raw LED power, even when using heavy-duty work gloves.

Peli™ 2315Z0 - SEE THE LIGHT AT THE END OF THE TUNNEL

- Built Peli tough
- 2 AA Batteries (included)
- ATEX Safety Certified Zone 0 (Cat. 1)
- Integrated Clip
- Full / Momentary Activation Tail Switch
- IPX8 1m waterproof
- Helmet mount (included)




DIMENSIONS

Length	6.22" (15.8 cm)
--------	-----------------

MATERIALS

Body	ABS
O-Ring	NBR
Lens	PC
Shroud	ABS
Clip	ABS

COLOURS

 High Visibility Yellow
--

LIGHT SPECS

Lamp Type	LED
-----------	-----

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	2
Batteries Included	yes
Volts	3.0v

WEIGHT






Weight With Batteries	4.6 oz (130 gr)
Weight Without Batteries	2.8 oz (79 gr)

SWITCH

Switch Type	Momentary Push Button
Light Modes	High

CERTIFICATIONS

IECEX ia
ATEX Zone 0

FL1 STANDARD	HIGH
	115 LUMENS
	6h 0mins
	75m
	1403cd
	IPX8 (1m)

Peli
c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-19-24