



## 2010 SabreLite™

Meet the design that set the lighting standard for industrial safety and fire rescue. Our 2010 LED combines a traditional task light design with high performance LED technology and safety certifications. The rugged, lightweight polymer body incorporates a twist on/off lens shroud allowing for easy operation and superior impact resistance. The result? Possibly the toughest flashlight available on the market today.

- Twist on/off activation
- Waterproof IPX7
- 22-hour runtime
- 3 "C" Batteries (not included)
- Heavy-duty body clip
- Split ring and security lanyard



### DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 8.11" (20.6 cm) |
|---------------|-----------------|

### MATERIALS

|                                |                                |
|--------------------------------|--------------------------------|
| <b>Body</b>                    | EXL                            |
| <b>O-Ring</b>                  | Ethylene Propylene             |
| <b>Lens</b>                    | Polycarbonate (PC)             |
| <b>Shroud</b>                  | ABS                            |
| <b>Clip</b>                    | ABS                            |
| <b>Contact Spring Retainer</b> | Stainless Steel / Brass Nickel |

### COLOURS

|  |
|--|
|  High Visibility Yellow |
|--|

### LIGHT SPECS

|                  |     |
|------------------|-----|
| <b>Lamp Type</b> | LED |
|------------------|-----|

### POWER

|                         |          |
|-------------------------|----------|
| <b>Battery Size</b>     | C        |
| <b>Battery Type</b>     | Alkaline |
| <b>Battery Quantity</b> | 3        |
| <b>Volts</b>            | 4.5v     |

### WEIGHT

|                                 |                  |
|---------------------------------|------------------|
| <b>Weight With Batteries</b>    | 13.4 oz (380 gr) |
| <b>Weight Without Batteries</b> | 5.4 oz (153 gr)  |
| <b>Packaged Weight</b>          | 7.0 oz (198 gr)  |

SWITCH






|                    |   |
|--------------------|---|
|                    | <b>Peli</b>   |
| <b>Switch Type</b> | c/ Provenca, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  |
| <b>Light Modes</b> | Twisting Lens Shroud<br><a href="mailto:info@peli.com">info@peli.com</a> • <a href="http://www.peli.com">www.peli.com</a><br>On / Off |
|                    | Document created on 06-01-24  |

CERTIFICATIONS

|                              |
|------------------------------|
| <b>Class I, Division 1</b>   |
| <b>Class II, Division 1</b>  |
| <b>Class III, Division 1</b> |

OTHER

|                     |     |
|---------------------|-----|
| <b>Submersible</b>  | yes |
| <b>Minimum Pack</b> | 1   |
| <b>Military</b>     | yes |
| <b>Package Code</b> | C   |

| FL1 STANDARD  | HIGH          |
|---|---------------|
|    | 161<br>LUMENS |
|  | 22h 0mins     |
|  | 160m          |
|  | 6398cd        |
|  | IPX7          |

ACCESSORIES