



1450EU

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1450EU
Standard



1450NF
No Foam



1450WF
With Foam



1454
With Padded Dividers

DIMENSIONS

Interior (L×W×D)	14.72 x 10.22" x 6.08 (37.4 x 26 x 15.4 cm)
Exterior (L×W×D)	16.10 x 13.03" x 6.88 (40.9 x 33.1 x 17.5 cm)
Lid Depth	1.75" (4.4 cm)
Bottom Depth	4.37" (11.1 cm)
Total Depth	6.12" (15.5 cm)
Int Volume	0.53 ft ³ (0.015 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane

Purge Body
Purge Vent

ABS
3 Micron Hydrophobic Non-Woven

COLOURS

 Black	 Desert Tan	 Orange	 OD Green
 Silver	 Yellow		

WEIGHT

Weight With Foam	6.39 lbs (2.9 kg)
Weight Empty	5.51 lbs (2.5 kg)
Buoyancy	30.00 lbs (13.6 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41

OTHER

Master Pack	4
Nameplate	yes
Military	yes

ACCESSORIES



1451
3 pc. Replacement Foam Set



1453
Replacement O-ring



1455
Padded Divider Set



1450PF
Special Application Panel
Frame




1450TPKIT
TrekPak Case Divider Kit



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-20-24