



9490

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
- Up to 6,000 lumens (calculated)
- Up to 24 hrs of run time
- Intelligent Control (allows for various light output levels)



DIMENSIONS

| | |
|--------------------------------|-----------------------------------------------|
| Head (LxWxD) | 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm) |
| Closed (LxWxD) | 20.00 x 6.50" x 11.25 (50.8 x 16.5 x 28.6 cm) |
| Light Head Height (max) | 72.00" (182.9 cm) |

MATERIALS

| | |
|-------------|--------------------|
| Body | Polypropylene |
| Head | Aluminum |
| Mast | Aluminum |
| Lens | Polycarbonate (PC) |

COLOURS

| | |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
|  Black |  Yellow |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|

LIGHT SPECS

| | |
|-----------------------|------|
| Lumens (High) | 6000 |
| Lamp Heads | 1 |
| Lamp Type | LED |
| Number of LEDs | 10 |
| Beam Spread | 125° |
| IP Rating | 54 |

POWER

| | |
|-------------------------|------------------------|
| Run Time (High) | 3.50 hrs |
| Run Time (Med) | 12.00 hrs |
| Run Time (Low) | 24.00 hrs |
| Battery Type | Sealed Lead Acid (SLA) |
| Rechargeable | yes |
| Battery Lifespan | 500 cycles |

| | |
|--------------------------------|----------------------------------------------------------------------------|
| Charge Time | 8 hrs |
| Battery Level Indicator | Full-time battery level display and low battery warning (visible flashing) |
| Sockets (Primary) | 1 |
| Volts | 12.0v |

WEIGHT

| | |
|---------------|---------------------|
| Weight | 32.00 lbs (14.5 kg) |
|---------------|---------------------|

SWITCH

| | |
|--------------------|--------------------------------|
| Switch Type | Silicone Rubber Keypad |
| Light Modes | High / Medium / Low / Flashing |

ACCESSORIES



9483
Power Supply



9487
Padded Shoulder Strap



9489
Powerpack



9447
DC Vehicle Charger Cord

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-16-24