



1620EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Strong polyurethane wheels with stainless steel bearings**
- **Watertight, crushproof, and dustproof**
- 4 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Made in Germany



CONFIGURATIONS



1620EU
Standard



1624
With Padded Dividers



1620NF
No Foam



1620WF
With Foam

DIMENSIONS

| | |
|------------------------------|--|
| Interior (L×W×D) | 21.37 x 16.31" x 12.56 (54.3 x 41.4 x 31.9 cm) |
| Exterior (L×W×D) | 24.81 x 19.37" x 13.87 (63 x 49.2 x 35.2 cm) |
| Lid Depth | 2.06" (5.2 cm) |
| Bottom Depth | 10.50" (26.7 cm) |
| Total Depth | 12.56" (31.9 cm) |
| Int Volume | 2.53 ft³ (0.072 m³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| | |
|---------------|---------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |

| | |
|-------------------|--------------------------------|
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

Black

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 26.01 lbs (11.8 kg) |
| Weight Empty | 24.47 lbs (11.1 kg) |
| Buoyancy | 149.91 lbs (68 kg) |
| Master Pack Weight | 26.90 lbs (12.2 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41

OTHER

| | |
|--------------------------|-----|
| Wheels | 2 |
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1609
Lid Organizer



1621
6 pc. Replacement Foam Set



1623
Replacement O-ring



1625
Padded Divider Set



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 05-19-24